


**Döcke PREMIUM Ventilation outlet ISL-125/700/ Cap**
**1. Product description and usage.**

Döcke PREMIUM ventilation outlet ISL-125/700/ Cap (further – «product») designed for traction enhancement within a pipe and for protection from precipitation and dirt. The product is installed onto pass-through element for the corresponding type of roof cover. The kit includes: the product, a set of screws in matching color.


**2. Geometrical parameters (without a cap).**

№	Indicators description, units measurements	Value
1	Height, mm	290
2	Max. diameter, mm	286
3	Area for diameter, mm	167

**3. Physical and mechanical properties.**

№	Indicators description, units measurements	Value
1	Operating temperature range, °C	from -40 to +80
2	Impact resistance at t - 20°C	yes
3	Resistance to UV impact	yes
4	Raw material	polypropylene

**4. Logistic characteristics.**

№	Indicators description, units measurements	Value
1	Weight 1 piece, kg	1,42
2	Quantity in a package, pcs	1
3	Package dimensions (LxWxH), mm	288x288x233

**5. Characteristics of the completed fixture.**

№	Unit	Quantity, pcs
1	Painted roofing self-tapping screw with a press washer 4.8x25 mm and with a hexagon head 8 mm (for fixing the base)	4

**6. Rules of storage.**

- Transportation of products should be performed on vehicles with covered or tilted bodies.
- The goods must be stored only within manufacturer's original packaging
- The goods must be stored in conditions that prevent contact with moist and direct sunlight
- The goods must be stored only in indoor ventilated space, at temperature from -35°C to +50°C and relative air humidity 50-60%.
- In case of long-term storage (over 10 days) it is necessary to use pallets or racks. The height of boxes or packages stacked on top of each other must not exceed 1,5 meters.
- Strictly prohibited to store products:
  - without original packaging;
  - under direct sunlight;
  - in 1 meter or closer to heating devices.

Technical support service: 8 800 100 71 45, [www.docke.ru](http://www.docke.ru).